

# HD-SDI Terminal Board (BNC)

# TY-FB9HD

## Product summary

- Enables viewing of digital High definition images from digital video equipment on a plasma display, using a terminal board compatible with the SDI system used by facilities such as broadcasting stations.
- Currently there is no support for embedded audio.

## Product specification (design and specification subject to change without notice)

Slot Compatibility	
2 Slot model	Slot 1, Slot 2
3 Slot model	Slot 1, Slot 2 (Slot 3 is not compatible)
INPUT	
HD-SDI IN	BNC x 1 :0.8 Vp-p (75 Ω)
HD-SDI OUT	BNC x 1 :Active through
Standards compliance	SMPTE 292M / SMPTE 259M-C
Compatible video format	525/59.94i, 625/50i, 750/60p : 59.94p, 750/50p, 1125/30p, 1125/24p, 1125/25p, 1125/60i : 59.94i, 1125/50i, 1125/24sF : 23.98sF
Weight	approx. 250 g (0.55 lbs.)
Included Accessories	Terminal function label x 1, Screw x 4 Terminal board replacement instruction x 1, Operating Instruction x 1
Recommended cable	SD-SDI : 75 Ω coaxial cable 5C-SV HD-SDI : 75 Ω coaxial cable 5C-FB
Maximum extension length	SD-SDI : 200 m HD-SDI : 100 m when using the above recommended cable

## Dimensions

Cautions: This drawing is not a scale.  
Units : mm (inches)

