Touch panel

TY-TP42P10S

■Product summary

A touch panel compatible with a 42-inch plasma display, this device achieves the high resolution of Approx. 32 000 x 18 000 while maintaining an extremely thin and compact design.

With a built-in USB interface, the touch panel can be easily connected to peripheral devices of equipment such as personal computers.

■ Product specifications (Design and specifications are subject to change without notice)

Spec	
Detection system	Infrared ray interruption
Panel aperture (W x H)	938 mm (W) x 538 mm (H) (36.9" x 21.2")
Detection range (W x H)	920 mm (W) x 518 mm (H) (36.2" x 20.4")
Effective detection range	920 mm (W) x 518 mm (H) (36.2" x 20.4")
Operation modes	Input point, Continuous, End point detection
Resolution (W x H)	32 000 (W) x 18 000 (H) points *1
Output system	Coordinate output
Optical elements	Infrared LED 4 pcs, CMOS image sensor 2 pcs
Minimum detection size	7 mm (0.3")
Responce rate	100 points / sec.
Interface Spec	<u> </u>
Interface	USB 2.0 full spead device
Compliant signal	+DATA, -DATA, VCC, GND
I/F Connector	TYPE B
Structure	
Panel shape	Flat panel
Dimensions (W x H x D)	1 016.4 mm (W) x 686 mm (H) x 47.9 mm (D) (40" X 26.9" x 1.9")
	(Except bracket, Inclusive of protruding portion)
Weight	4.1 kg (9.0lbs) (Except bracket)
Escutcheon (frame)	Aluminum
Environment	
Temperature	Operation 0 to 40 °C (Temperature gradient) *2
Humidity	Operation 20 to 80 % (No dewing) *2
Resistance to external light	Lateral light 2 000 lx + 20 % (20° angle of incidence)
	Frontal light 10 000 lx + 20 % (90° angle of incidence)
Main unit	
Power supply (voltage)	DC + 5 V ± 10 % (Supplied from USB bus power)
Electric current	DC + 5 V max. 450 mA

^{*1 :} Resolution obtained by using a dedicated driver software.

Accessories

- USB Cable CD-ROM Operating instructions Ferrit core Tuch pen Mounting bracket (A) (B)
- Mounting bracket (B) Vertical mounting bracket USB cable anchor Mounting screws (A) (B)
- Tuch pen Velcro strip Ruber feet
- USB driver touch panel setting program (apricable OS : Microsoft, Windows 2000, Windows XP, Windows Vista (32 bit))

^{*2:} When the panel is attached to plasma display produced by Matsushita Electric Industrial Co., Ltd.



