



Wireless Module ET-WM200

● Product specification (design and specification subject to change without notice)

Power supply	Supplied from the display.
Standard	IEEE802.11b/g/n
Modulation	Direct sequence spread spectrum (DSSS) system, Orthogonal frequency division multiplex (OFDM) system
Transmission speed (standard)*1	IEEE802.11b : Up to 11 Mbps, IEEE802.11g : Up to 54 Mbps, IEEE802.11n : Up to 150 Mbps
Frequency range (channel)	2412 - 2472 MHz (1 - 13 ch)
Access method	Infrastructure mode, ad-hoc mode*2
Security	WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES), WEP(128 bit/64 bit) When mounted on the display: PEAP(MS-CHAPv2), PEAP(GTC), EAP-TTLS(MD5), EAP-TTLS(MS-CHAPv2), EAP-FAST(MS-CHAPv2), EAP-FAST(GTC), EAP-TLS
Antenna	T x 1, R x 1
Interface	USB 2.0 (Cannot be used with any projector other than a Panasonic display with ET-WM200 compatibility.)
Dimensions (W x H x D)	approx. 23 x 9 x 63 mm (29/32" x 11/32" x 2-15/32")
Weight	approx. 10g (0.4 oz)*3
Operating environment*4	Temperature: 0°C - 45°C (32° - 113°F) Humidity: 20% - 80 % (no condensation)
Supplied accessory	Wireless Manager ME 5.5, CD-ROM x 1

*1 This is a theoretical speed. The actual transfer speed varies depending on the usage environment and connected devices.

*2 Not supported by IEEE802.11n.

*3 Average value. May differ depending on models.

*4 Conforms to the environmental conditions of the mounted display.

● DIMENSIONS

Cautions: This drawing is not a scale
Units : mm

