

Component Video Terminal Board (BNC)

TY-42TM6A

Product summary

Enables connection of devices with component output terminals, such as digital BS tuners, STBs or DVD players.

Product specification (Design and specifications subject to change without notice)

Mass	Approx. 250 g					
Accessories	<ul style="list-style-type: none"> • Terminal function label (x1) • Slot cover (x1) • Terminal board replacement instructions • Screws (x4) 					
Slot Number	<table border="1" style="width: 100%;"> <tr> <td>2 slots model</td> <td>Slot 1, Slot 2</td> </tr> <tr> <td>3 slots model</td> <td>Slot 1, Slot 2, Slot 3</td> </tr> </table>	2 slots model	Slot 1, Slot 2	3 slots model	Slot 1, Slot 2, Slot 3	
2 slots model	Slot 1, Slot 2					
3 slots model	Slot 1, Slot 2, Slot 3					
Terminal specification	<p>Component Video/RGB input</p> <ul style="list-style-type: none"> • Y/G (BNC) : 1.0 V [p-p] with sync signal (75-ohm) • PB, PR/CB, CR (BNC) : 0.7 V [p-p] (75-ohm) • R/B (BNC) : 0.7 V [p-p] (75-ohm) • AUDIO IN L/R (RCA PIN JACK x 2) : 0.5 V [rms] (high impedance) 					

Signal table

	Signal	Horizontal frequency (kHz)	Vertical frequency (Hz)
1	525 (480) / 60i	15.73	59.94
2	525 (480) / 60p	31.47	59.94
3	625 (575) / 50i	15.63	50.00
4	625 (575) / 50p	31.25	50.00
5	750 (720) / 60p	45.00	60.00
6	750 (720) / 50p	37.50	50.00
7	1,125 (1,080) / 60i	33.75	59.94
8	1,125 (1,080) / 50i	28.13	50.00
9	1,125 (1,080) / 24p	27.00	24.00
10	1,125 (1,080) / 24sF	27.00	48.00
11	1,250 (1,080) / 50i	31.25	50.00

Dimensions

Units : (mm)

