

Component Video Terminal Board (RCA)

TY-42TM6Z

Product summary

Enables connection of devices with component output terminals, such as digital BS tuners, STBs or DVD players.

Product specification

(Design and specifications subject to change without notice)

Mass	Approx. 250 g	
Accessories	<ul style="list-style-type: none"> • Terminal function label (x1) • Terminal board replacement instructions • Slot cover (x1) • Screws (x4) 	
Slot Number	2 slots model	Slot 1, Slot 2
	3 slots model	Slot 1, Slot 2, Slot 3
Terminal specification	Component/Video/RGB input <ul style="list-style-type: none"> • Y/G : 1.0 V [p-p] / composite (75-ohm) • PB, PR/CB, CR : 0.7 V [p-p] (75-ohm) • R/B : 0.7 V [p-p] (75-ohm) • AUDIO IN L/R (RCA PIN JACK x 2) : 0.5 V [rms] (high impedance) 	

Signal table

	Signal	Horizontal frequency (kHz)	Vertical frequency (Hz)
1	525 (480) / 60i	15.73	59.94
2	525 (480) / 60p	31.47	59.94
3	625 (575) / 50i	15.63	50.00
4	625 (575) / 50p	31.25	50.00
5	750 (720) / 60p	45.00	60.00
6	750 (720) / 50p	37.50	50.00
7	1,125 (1,080) / 60i	33.75	59.94
8	1,125 (1,080) / 50i	28.13	50.00
9	1,125 (1,080) / 24p	27.00	24.00
10	1,125 (1,080) / 24sF	27.00	48.00
11	1,250 (1,080) / 50i	31.25	50.00

Dimensions

