



PROJECTOR

LS710HD

Key Features


- 2nd generation laser phosphor technology with up to 30,000 hours lifespan
- 4,200 ANSI Lumens offering bright images in any environment
- Up to 300" ultra large screen that is easily installed and set up
- 0.49 short throw for immersive edge blending without any shadows
- Installation flexibility: H/V keystone, 4 corner adjustment, 360° projection and portrait mode



Product Description

The Luminous Superior series is ViewSonic's lamp-free high brightness projector for both business and education. The LS710HD adopts industry-leading 2nd generation laser phosphor technology, delivers 4,200 ANSI Lumens while eliminating the use of toxic mercury, reducing the cost and effort of frequent lamp replacement and lowering total cost of ownership. The lamp-free light source offers enhanced sustainability for a greener environment while delivering clear and bright images with vivid colors and 1080p resolution. Boasting short throw ratio, flexible installation and easy image adjustments, the projector enables effortless edge blending to create an immersive experience for any space, be it a restaurant, gym, gallery, etc. With 0.49 short throw ratio, the projector can provide 100" large screen size from only 1.1 m away without being bothered by the shadows.

The LS710HD allows perfectly-shaped images even from an angled projection with H/V keystone and 4 corner correction and offers versatile application with 360° projection and portrait mode. The projector also comes with HDMI 2.0b, ensuring you access to original 4K quality content with HDR/HLG support.



- 1. Front IR
- 2. Lens
- 3. HDMI 1.4/ HDCP 1.4
- 4. HDMI 2.0/ HDCP 2.2
- 5. USB-A (5V/1.5A, Service)
- 6. Audio Out
- 7. RJ45 (LAN Control)

- 8. RS232
- 9. Focus Ring
- 10. LED Indicator
- 11. Power Button
- 12. Keypad & IR

Visit Us www.viewsonic.com

SPECIFICATION

Native Resolution:	1920x1080
Brightness:	4200 (ANSI Lumens)
Contrast Ratio:	3000000:1
Display Color:	1.07 Billion Colors
Light Source Type:	Laser Phosphor
Light Source Life (hours) with Normal Mode:	20000
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)
Lens:	F=2.8, f=7.51mm
Projection Offset:	132%+/-5%
Throw Ratio:	0.49
Optical Zoom:	Fixed
Digital Zoom:	0.8x-2.0x
Image Size:	40"-300"
Throw Distance:	0.43-3.25m (100"@1.08m)
Keystone:	H: +/-15° , V: +/-15°
Audible Noise (Normal):	32dB
Audible Noise (Eco):	29dB
Input Lag:	49.9ms
Resolution Support:	VGA(640 x 480) to 4K UHD(3840 x 2160)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4K UHD
Horizontal Frequency:	15K-102KHz
Vertical Scan Rate:	23-120Hz

INPUT

HDMI:	2 (HDMI 2.0/ HDCP 2.2 HDMI 1.4/ HDCP 1.4)
-------	---

OUTPUT

Audio-out (3.5mm):	1
Speaker:	15W x2
USB Type A (Power):	1 (5V/1.5A)

CONTROL

RS232 (DB 9-pin male):	1
RJ45 (LAN control):	1
USB Type A (Services):	1 (share with USB A Output)

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz (AC in)
Power Consumption:	Normal: 245W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	4.5kg
Gross Weight:	6.6kg
Dimensions (WxDxH) with Adjustment Foot:	337x265x131.5mm
Packing Dimensions:	496x195x387mm
OSD Language:	English, French, German, Spanish, Italian, Portuguese, Dutch, Swedish, Finnish, Greek, Norwegian/Danish, Polish, Russian, Simplified_Chinese, Traditional_Chinese, Korean, Arabic, Japanese, Thai, Hungarian, Czechoslovak, Turkish, Farsi, Vietnamese, Indonesian, Romanian, Slovakian, total 27 languages
User Guide Language:	English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
STANDARD ACCESSORY	
Power Cord:	1
Remote Control:	1
QSG:	Yes
Warranty Card:	Yes (CN Only)
OPTIONAL ACCESSORY	
Wall/Ceiling Mount:	PJ-WMK-007