Key Features

- 4K HDR professional-quality visuals
- 6,000 ANSI Lumens offering bright images in any environment
- Up to a 300" ultra-large screen with a lower cost-perinch
- Supports a 21:9 aspect ratio, ideal for Microsoft Teams
 Rooms
- Installation flexibility: H/V lens shift, 1.6x optical zoom, and H/V keystone correction



Product **Description**

The LSC601-4K is a lamp-free, high-brightness projector designed for commercial, educational, and public spaces. Equipped with 4K resolution and HDR/HLG support, it delivers professional-quality presentations and stunning visuals. Utilizing 2nd generation laser phosphor technology, this projector offers 6,000 ANSI Lumens of brightness for up to 30,000 hours and can project an ultra-large screen up to 300". Ideal for modern workplaces, its 21:9 aspect ratio is optimized for Microsoft Teams Rooms applications, enhancing collaborative environments. Equipped with features like H/V lens shift, 1.6x optical zoom, H/V keystone correction, and 360° projection capabilities, the LSC601-4K offers flexible setup possibilities. Additionally, its comprehensive LAN control ensures seamless integration into existing device management networks.

- 1. Zoom Ring
- 2. Focus Ring
- 3. Front IR
- 4. S/PDIF
- 5. USB-A (5V/2A) 6. HDMI 2.0/HDCP 2.2
- 7. USB-A (5V/2A)
- 8. RS232
- 9. Audio Out
- 10. Rear IR
- 11. RJ45
- 12. HDBaseT
- 13. AC In
- 14. LED Indicator
- 15. Kevpad
- 16. Lens Shift Control Knob x2
- 17. Power Button

Visit Us www.viewsonic.com



SPECIFICATION

SPECIFICATION	
Native Resolution:	WUXGA with 4K Enhancement
Brightness:	6000 (ANSI Lumens)
Brightness (Center Lumens):	6500
Contrast Ratio:	500:1
Display Color:	1.07 Billion Colors
Light Source Type:	Laser Phosphor
Light Source Life (hours) with Normal Mode:	20000
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)
Lens:	F=1.5-2.08, f=17.2-27.7mm
Projection Offset:	0%+/-5%
Throw Ratio:	1.2-2.01
Optical Zoom:	1.6X
Digital Zoom:	1.0x-2.0x
Image Size:	30"-300"
Throw Distance:	0.80-13.35m (100"@2.66m)
Keystone:	H:+/-25° , V:+/-30°
Lens Shift V. Range:	+66%, 0%
Lens Shift H. Range:	+29%, -29%
Audible Noise (Normal):	37dB
Audible Noise (Eco):	26dB
Input Lag:	32ms
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p
Horizontal Frequency:	15K-135KHz
Vertical Scan Rate:	24-85Hz
INPUT	
HDMI:	2 (HDMI 2.0, HDCP 1.4/2.2)
Audio-in (3.5mm):	1
USB Type A:	2 (5V/2A)
HDBaseT:	1
RJ45 Input (Internet):	Yes
OUTPUT	
Audio-out (3.5mm):	1
Audio-out (HDMI ARC):	1 (Share with HDMI Input)
S/PDIF:	1
Speaker:	16W
USB Type A (Power):	2 (USB2.0 - 5V/2A, share with USB A Input)
CONTROL	
RS232 (DB 9-pin male):	1
RJ45 (LAN control):	1 (share with RJ45 Internet)
USB Type A (Services):	1 (share with USB A Output)

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz (AC in)
Power Consumption:	Normal: 325W Standby: <0.5W
Operating Temperature:	0~40℃
Carton:	Brown
Net Weight:	7.9kg
Gross Weight:	10.93kg
Dimensions (WxDxH) with Adjustment Foot:	405x358x137mm
Packing Dimensions:	510x498x260mm
OSD Language:	English, German, French, Italian, Spanish, Polish, Swedish, Dutch, Portugese, Japanese, Simplified Chinese, Traditional Chinese, Korean, Russian, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Vietnamese, Thai, total 23 languages
User Guide Language:	English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
STANDARD ACCESSORY	
Power Cord:	1

Power Cord:	1
Remote Control:	1
QSG:	Yes
Air Filter:	Yes
Warranty Card:	Yes (CN Only)

OPTIONAL ACCESSORY

Air Filter:	Yes
Wall/Ceiling Mount:	PJ-WMK-007