### **Key Features**

- Innovative home installation projector with RGB laser technology
- Unmatched color performance with 100% coverage of the BT.2020 color space
- 5,200 RGB Laser Lumens for uninterrupted bigscreen fun in any lighting condition
- True 4K HDR immersive visuals and high contrast enabled by a 0.65-inch DMD chip
- Flexible installation options: 1.6x optical zoom, vertical lens shift, and H/V keystone correction



## Product **Description**

The LX700-4K RGB projector sets a new standard in home cinema with its RGB laser technology, enhancing image quality for an exceptional viewing experience. Utilizing advanced laser projection, it achieves 100% BT.2020 color gamut coverage, delivering vivid, lifelike colors that bring your favorite shows to life. With 5,200 RGB Laser Lumens, 4K UHD resolution, and HDR/HLG support, it ensures a bright, crystal-clear, vibrant viewing experience at any time. The projector's high contrast ratio, powered by the Texas Instruments 0.65-inch DMD chip, reveals intricate details in dark scenes and enriches blacks for complete visual immersion. Its 1.6x optical zoom, vertical lens shift, and side projection capabilities, complemented by H/V keystone and 4-corner adjustment, offer versatile installation options, making setup and home cinema upgrades effortless. As one of the first "Designed for Xbox" projectors, it also provides outstanding gaming performance at an optimal 1440p@120Hz, ensuring total immersion in all your home entertainment pursuits.





# Visit Us www.viewsonic.com

#### **SPECIFICATION**

SPECIFICATION		(
Native Resolution:	3840x2160	
Brightness:	5200 (RGB Laser Lumens)	
Contrast Ratio:	3000000:1	
Display Color:	1.07 Billion Colors	
Light Source Type:	RGB Laser	
Light Source Life (hours) with Normal Mode:	20000	
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)	
Lens:	F=2.5-3.26, f=20.911- 32.62mm	
Projection Offset:	137%+/-10%	
Throw Ratio:	1.4-2.24	
Optical Zoom:	1.6x	
Digital Zoom:	0.8x-2.0x	
Image Size:	30"-300"	
Throw Distance:	0.93-14.88m \[ (100"@3.10m)	
Keystone:	H:+/-30° , V:+/-30°	
Lens Shift V. Range:	+0%, -15%	
Audible Noise (Normal):	30dB	
Audible Noise (Eco):	27dB	
Input Lag:	4.2ms	
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160)	
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p	5
Horizontal Frequency:	15K-255KHz	
Vertical Scan Rate:	23-240Hz	
INPUT		
HDMI:	2 (HDMI 2.0/ HDCP 2.2)	(
OUTPUT		
Audio-out (3.5mm):	1	ı
Audio-out (HDMI ARC):	1 (eARC) (Share with HDMI Input)	
Speaker:	15W	
USB Type A (Power):	2 (USB2.0 - 5V/0.5A x1, USB2.0 - 5V/1.5A x1, share with USB A Service)	
12V Trigger (3.5mm):	1	
CONTROL		
RS232 (DB 9-pin male):	1	
USB Type A (Services):	1 (share with USB A Output)	

OTHERS		
Power Supply Voltage:	Power adaptor: Input: 100~240V Output: 19.5VDC / 9.23A	
Power Consumption:	Normal: 145W Standby: <0.5W	
Operating Temperature:	0~40°C	
Carton:	Brown	
Net Weight:	2.70kg	
Gross Weight:	4.00kg	
Dimensions (WxDxH) with Adjustment Foot:	286x216x129mm	
Packing Dimensions:	400x280x155mm	
OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, Arabic, Vietnamese, Greek, Norsk. Total 23 languages	
User Guide Language:	English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages	
STANDARD ACCESSORY		
Power Cord:	1	
Remote Control:	1 (w/ backlit)	
QSG:	Yes	
Warranty Card: OPTIONAL ACCESSORY	Yes (CN Only)	
Wall/Ceiling Mount:	PJ-WMK-007	
Carry Bag:	PJ-CASE-008	